

**DESCRIPTION**

It is a series of 2-door stoves, with forced ventilation with the exterior made of acid-resistant and fire-painted steel sheet, while the internal part of the chamber, including internal part of the door, is made of AISI 304 stainless steel.

The thermal insulation, also present in the door, consists of rock wool panels.



The temperature control is entrusted to a K1PX type microprocessor programmer with which it is possible to set and memorize drying cycles consisting of a maximum of 8 STEPS or to set a working temperature that will remain until it is changed.


This series of stoves is built according to the latest safety regulations which require all electrical parts to be higher than 30 cm from the ground.

In this model they are all placed on the door, making any maintenance even easier.

The electrical equipment, built according to safety standards, is equipped with a programmer with which it is possible to set a drying cycle or set a working temperature that will remain operational until it is changed again.

**Chamber temperature variation:**

**3 ° C (The check is done at 150 ° C)**



MODEL	N°. MAX SHELVES	DISTANCE BETWEEN SHELVES [mm]	MAX WEIGHT [kG] (distributed)
VF 600/N	7	60	25
VF 940	12		
VF 1000			
VF 1300	15		
VF 1700			

**TECHNICAL CHARACTERISTICS**

Mod.	Temp. max	Internal dimensions [mm]			External dimensions [mm]			Power kW	V + N	Weight [kG]
		Width [a]	Depth [b]	Height [c]	Width [A]	Depth [B]	Height [C]			
VF 600/N	220 °C	1380	850	500	1680	1120	1250	6,5	400	320
VF 940		1380	850	800	1680	1270	1850			464
VF 1000		1500	850	800	1800	1150	1650	15		495
VF 1300		1150	1150	1000	1450	1410	1760			443
VF 1700		1300	1300	1000	1600	1560	1760			542

(all data are not binding, the manufacturer reserves the right to modify them)